

# Well Construction

## Frank's Tubular Running Services (TRS)

### RS-250™ Long Stroke Spider

#### Features and benefits

- Accommodate multiple control lines typically encountered on today's hightech completions.
- Easily handles large OD control umbilicals used on subsea completions.
- Allows for easy operation of equipment without the need for special scaffolding that is typically required with surface mount tools.
- Suitable on casing, completion tubing, or drill pipe applications. Corrosion resistant tubing can be run with Expro's slips and inserts.
- "Long Stroke" feature allows slips to be raised higher, therefore wider opening than conventional spider bodies to pass large OD completion assemblies without removing the spider.
- Options for control line/umbilical protection including COBRA™ Control Line Manipulator Arm, Control Line Pusher Arm, and Rotating Control Line Sleeve, Sheaveless Control Line Manipulator Arm.
- Fits into standard API 27-1/2" rotary table, allowing main body of the tool to be completely recessed into the rotary table.

#### Specifications

Weight	2,700 lbs (1,225 kgs)
Dimensions	27-9/16" (700mm) into rotary, 7-1/2" (190mm) above floor, 30" (762mm) OD
Pipe range	2-3/8" - 7-5/8"
Rated capacity	250 tons (227 tonnes)
Air pressure required	70 psi (4.8 bar)

For more information, please contact your Expro representative or email: [wellconstruction@expro.com](mailto:wellconstruction@expro.com)

